



| VOCE | A | B | L | G | a | D-Max | | |
|------|----|------|------|----------|-----|-------|-----|-----|
| | | | | | | ● | ● | ■ |
| CT2A | 11 | 14.5 | 53 | M10X0.8 | 16° | 7.5 | 6 | 5 |
| CT4 | 16 | 21 | 58 | M14X1.00 | 16° | 10.5 | 9 | 7.5 |
| CT4L | 16 | 20.5 | 59 | M14X1.00 | 16° | 12 | 9.5 | 8 |
| CT4B | 18 | 21.8 | 59 | M16X1.00 | 30° | 13 | 11 | 9 |
| CT5 | 22 | 29 | 68 | M19X1.00 | 16° | 16 | 14 | 11 |
| CT5C | 22 | 29 | 68 | M22X1.00 | 16° | 18 | 15 | 13 |
| CT5A | 24 | 30 | 61 | M24X1.00 | 30° | 16 | 14 | 11 |
| CT6D | 26 | 29 | 77 | M25X1.00 | 16° | 20 | 16 | 13 |
| CT6S | 28 | 34 | 82 | M25X1.00 | 16° | 21 | 18 | 15 |
| CT6T | 28 | 38 | 81 | M25X1.00 | 30° | 21 | 18 | 15 |
| CT6 | 32 | 39.8 | 71 | M32X1.00 | 30° | 22 | 19 | 15 |
| CT6A | 34 | 41 | 87.5 | M34X1.00 | 10° | 25 | 21 | 17 |
| CT7B | 42 | 49 | 82 | M40X1.00 | 16° | 32 | 26 | 21 |
| CT7S | 48 | 54 | 82 | M46X1.00 | 16° | 38 | - | - |

LUNGHEZZA DELLA GUIDA IN METALLO DURO

| Ø | X | | | | | | | | | | | |
|-------|-------------|-----------|-----------------------|------------------------|------------------------|------------------------|------------------------|------------------------|------------------------|------------------------|------------------------|------------------------|
| | Lg standard | Lg. media | Lg XL | | | | | | | | | |
| | | | CT4 | CT4B | CT5A | CT5C | CT6A | CT6D | CT6S | CT6T | CT7B | CT7S |
| 2-3 | 15 mm | 30 mm | | | | | | | | | | |
| 4 | 18 mm | 30 mm | | | | | | | | | | |
| 5-9 | 20 mm | 30 mm | | | | | | | | | | |
| 10-15 | 22 mm | 30 mm | | | | | | | | | | |
| 16-19 | 25 mm | 30 mm | | | | | | | | | | |
| 20-24 | 27 mm | 40 mm | 35 mm (da Ø 2 a 8) | 35 mm (da Ø 2 a 12) | 35 mm (da Ø 2 a 16) | 45 mm (da Ø 2 a 15) | 60 mm (da Ø 5 a 26) | 50 mm (da Ø 2 a 16) | 55 mm (da Ø 2 a 20) | 55 mm (da Ø 2 a 20) | 55 mm (da Ø 5 a 32) | 55 mm (da Ø 5 a 38) |
| 25-26 | 28 mm | 40 mm | | | | | | | | | | |
| 27 | 29 mm | 40 mm | | | | | | | | | | |
| 28-29 | 30 mm | 40 mm | | | | | | | | | | |
| 30-33 | 31 mm | 40 mm | | | | | | | | | | |
| 33-38 | 33 mm | 40 mm | | | | | | | | | | |

BUSSOLE SPECIALI

OPZIONI

- Lunghezza guida maggiorata o su misura
- Sigillatura anti-truciolo
- Rivestimento anti-attrito TiN
- Intagli a zig zag